

bio reme®
Bioculture



Greencraft Labs
Private Limited

FOG

WHAT IS BIO REME FOG?

Bio Reme FOG is a combination of highly active microbes that are designed to accelerate liquefaction and digestion of food-based Fats, Oils and Greases (also known as "FOG:") found in grease traps, collection systems and wastewater treatment systems (activated sludge, RBC, DAF, etc). These isolated microbial strains contains a specially formulated range of adapted high-performance microorganisms such as 4 gram-positive Bacillus strains and 4 gram-negative vegetative strains for Rapid grease digester for drains, septic tanks and 10 gram-positive Bacillus strains and 4 gram-negative strains for Industrial grease digester along with 6 gram-positive Bacillus strains and 5 gram-negative strains for Severe grease control in lift stations, sump pumps, wet wells, large hotel and restaurant grease traps.

Bio Reme FOG specially developed for the use in the biological wastewater treatment with a high content of greases, fats and oils. Bio Reme contains surface tension depressants and penetrants that loose and liquefy heavy grease deposits, thereby assisting the biodegradation. Degradation of Fat oil & grease begins with the breakdown of the complex molecule by extracellular enzymes produced by Bio Reme microorganisms. Microorganisms produce various classes of lipolytic enzymes including true lipases and esterase's (carboxylesterases). Other compounds produced by microorganisms and are useful in the process of biodegradation of FOG and biosurfactants, etc. After the FOG has been exposed to the bio surfactant further the fatty acids and glycerol are consumed by the Bio Reme microorganisms that are capable of utilizing them.





FATS

Fats are composed of esters of glycerol and fatty acids. Bacteria utilize fats after the hydrolysis of the ester bond. Extracellular enzymes, called esterases and lipases, are responsible for this reaction. The end result is the formation of glycerol and free fatty acids. After fatty acids are liberated by the enzymatic action of esterase and lipase, the next step in the breakdown is called Beta Oxidation, a process in which two carbons split off at a time. The first step in the oxidation of fatty acids is initiated by Coenzyme A, leading to the release of Acetyl Co-A, that results into a fatty acid which is reduced by two carbons. This process is then repeated, following the Tricarboxylic acid cycle until the end results are carbon dioxide and water or they follow the glyoxylate pathway producing additional cell constituents.

The grease and fats are degraded completely by this method, not just solubilized to move downstream causing trouble in the collection systems or municipal waste treatment plants. Bio Reme FOG degrades formulations of utilize microbes that produces esterase, lipase and fatty acid degradation together with catalysts that enhances the performance. Using a pure surfactant to demonstrate apparent solubilization of foods, fats and oils are "magic trick" that does not demonstrate a true breakdown of fats and oils. To verify esterase and lipase enzyme activity, use Bio Reme FOG and see results of lipase & esterase test results. 8 strains of gram-positive Bacillus in a Powder formula degrade food fats and grease and oxidizes hydrogen sulphide odor in wet wells, grease traps, sump pumps and waste loading zone. Improved grease digestion! No unpleasant odor for home use in drains. Improved sulphide oxidation, grease degrading and fatty acid degrading.



Benefits of Bio Reme FOG

- Degrades Fat Oil & Grease from waste water.
- Reduces accumulation of organic matter on the surface of tank.
- Breakdowns complex chain molecular structure of oil into simpler form.
- Reduces foaming in biological tank.
- Multiple strains of bacteria for effective result.
- Reduces odour from plant.
- Improves overall efficiency of the plant.
- Effective under most of the environmental conditions.
- Easy to store, handle and transport.

Area of Application

- Membrane Bio reactor
- Activated sludge Process
- Sequencing batch reactor
- Moving bed bio reactor
- Extended Aeration system
- Oil & grease Trap

Performance Properties

| | |
|--------------------------|------------------------------|
| pH | 6.5-7.5 |
| Temperature | 5 to 55°C |
| Reactivation Rate | 99 % after addition to water |
| Concentration | Highly Concentrated |
| Shelf Life | 2 years |

Application Matrix

- Mix Bio Reme 1 kg powder in 20 Liter water (Prefer normal temperature).
- Stir well and remain in bucket for 30 minutes (for bacteria activation)
- Directly Dose at inlet of tank.

Physical Properties

| | |
|-------------------------|-------------------------|
| Appearance | Off White Colour |
| Physical State | Powdered Form |
| Odour | Odourless |
| Moisture Content | 6-7 % |
| Mesh Size | 0.6 mm |
| Packaging | 1 kg Aluminium zip lock |

Dosage Schedule

Depend upon the FOG content, contaminants and volume of waste water.



Testing & Certifications

- ✓ Certified Non Toxic
- ✓ Certified Temperature Range
- ✓ Certified Non GMO
- ✓ Certified Non Pathogenic
- ✓ Tested for Toxic Metals
- ✓ Bioassay on Fish Done

MAHARASHTRA- PUNE

R05, Gulmarg,
Pune-Mumbai Highway,
Baner, Pune-411045
+91-9023882028
+91-9503051200
sales@greencraftlabs.in

NEW DELHI

216, Jaina Tower
2, District centre,
Janakpuri -110058,
New Delhi
+91-9503653500
+91-7488567070
sales@greencraftlabs.in

PHILIPPINES

No. 21 Emerald St., Silverland,
Quezon City, Philippines
+63 2 275 7206
+63 02 8275 7206
anil@greencraftlabs.in

